

Data Sheet | Item Number: 787-732

Power supply; Eco; 1-phase; 24 VDC output voltage; 10 A output current; DC-OK LED; 4,00 mm²

<https://www.wago.com/787-732>



Features:

- Switched-mode power supply
- Natural convection cooling when horizontally mounted
- Encapsulated for use in control cabinets
- Suitable for both parallel and series operation
- Electrically isolated output voltage (SELV) per UL 60950-1; PELV per EN 60204

Connection data

| | |
|--------------------------------|--------------------------------------------|
| Connection type 1 | Input/output |
| Connection technology | CAGE CLAMP® |
| WAGO connector | WAGO 745 Series |
| Solid conductor | 0.08 ... 4 mm ² / 28 ... 12 AWG |
| Fine-stranded conductor | 0.08 ... 4 mm ² / 28 ... 12 AWG |
| Strip length | 8 ... 9 mm / 0.31 ... 0.35 inches |
| Note (conductor cross-section) | 12 AWG: THHN, THWN |

Physical data

| | |
|-----------------------------------|-----------------------|
| Width | 110 mm / 4.331 inches |
| Height | 136 mm / 5.354 inches |
| Depth from upper-edge of DIN-rail | 92 mm / 3.622 inches |

Material data

| | |
|-----------|---------|
| Fire load | 10.1 MJ |
| Weight | 1200 g |

Commercial data

| | |
|-----------------------|--------------------------|
| Product Group | 6 (INTERFACE ELECTRONIC) |
| eCl@ss 10.0 | 27-04-07-01 |
| eCl@ss 9.0 | 27-04-07-01 |
| ETIM 9.0 | EC002540 |
| ETIM 8.0 | EC002540 |
| PU (SPU) | 1 pcs |
| Packaging type | Box |
| Country of origin | CN |
| GTIN | 4045454908140 |
| Customs tariff number | 85044083900 |

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com